

00

000 00-0000-0 000000 0000 0000 00 00000 00000 00000 0000 0 00 0000 00000 00 00 0000 0000 00000. 0 0000 00 0000 00 00 00000 00 55mm 0000 0000 0000 0 00 00 0000 00000.

0 00 0000 0 00000 00 600 00000 0000 0 00000 00000 00000 00000 0 00000000. 0000 000000 0 00 00 0000 00000 0 00000 00 0 00 00 0 00000. 0000 0000 0000 00000 00000 00000 00000 00 0 0 00 0000 000000. 00 0000 0000 00 00000 00 00 0 00000000 00 0000 0 00000. 00000 00 00000 00000 0 00000 0000 0 00000.

00	0000 00 00 0000 0000 0 0000
00	000000/0000
00 00.	PV-0035-09
00 00	L3150*H415*W390mm 00 0000.
00	00 00 0000.
0000	18KG/18.5KG
00 00000	100/00 0/00
00	900 0000
00 00	00 00 / 00 00
00000000	00 0000 0
00 00	7-120

0 00-00 0000 0-00

00 00.	00	0	00	00
PV-0035-02	0000 20	415mm	700mm	390mm
PV-0035-03	0000 30	415mm	1050mm	390mm
PV-0035-04	4 000	415mm	1400mm	390mm
PV-0035-05	5 000	415mm	1750mm	390mm
PV-0035-06	6 000	415mm	2100mm	390mm

00

- >Strong steel construction
- >Hot dip galvanised and siteel frame for long life
- >Suitable for tyre widths up to 55mm,suitable for floor fixing
- >Accessible from both sides
- >Simple self assembly required and accessible from both sides
- >415h x 390d x 350w mm between wheels,19mm dia. tubular wheel supports

□□



□□

□□ □□	* ISO □□
	* 1 □□ □□ □□
	* □□ : □□□□ □□□ 3~5□, □□□□ □□□ 10~15□
	* □□, □□ □ □□ □□ □□ □□□□ □□.

□□□□ □□:

1. □□□ □□□ □□□ □ □□□□?

-□□□□. □□ □□□□ □□□□ □□ □□□ □□□□ □□□ □□□□□□.

2. □□□ □□ □□□ □□□ □□ □ □□□□?

-□□ □□□□ □□□ □□ □□□□ □□□ □□□□ □□□□.

3. □□□ □□□ □□□ □ □□□?

-□□□ □□□ □□□□□! □□□ □□□ □ □□ □□□ □ □□□ □□□ □□□ □□□ □□□ □□□ □□□.

4. □□□ □□□□□ □□□□□?

-□□□□□ □□□ □□ 7□□□, □□ □□□ □□ 30□□□□□ □□□□□.

[□□□ □□□ □□□ □□□ □□□ □□□□□□□!](#)